

## United States Patent and Trademark Office



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.		
10/541,352	07/05/2005	Gerhard Jonke	2002P00148WOUS	8235		
28204 SIEMENS SC	7590 01/23/2007 HWEIZ AG	EXAMINER				
I-47, INTELLECTUAL PROPERTY			CABRERA, ZOILA E			
ALBISRIEDE ZURICH, CH-	RSTRASSE 245 -8047	ART UNIT	PAPER NUMBER			
SWITZERLAI		2125				
				· .		
SHORTENED STATUTO	RY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE			
3 MONTHS		01/23/2007	PAT	DADED		

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

Office Action Summary		Application	Application No. Applicant(s)					
		10/541,352		JONKE ET AL.				
		Examiner		Art Unit				
		Zoila E. Cabr		2125				
Period fo	The MAILING DATE of this communication a or Reply	appears on the co	over sheet with the c	orrespondence ad	ddress			
WHIC - Exte after - If NC - Failu Any	ORTENED STATUTORY PERIOD FOR REP CHEVER IS LONGER, FROM THE MAILING nsions of time may be available under the provisions of 37 CFR SIX (6) MONTHS from the mailing date of this communication. O period for reply is specified above, the maximum statutory perior to reply within the set or extended period for reply will, by state reply received by the Office later than three months after the may ed patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS 1.136(a). In no event, od will apply and will ex tute, cause the applicat	COMMUNICATION however, may a reply be tim pire SIX (6) MONTHS from to become ABANDONED	L. ely filed the mailing date of this of (35 U.S.C. § 133).	,			
Status								
1)	Responsive to communication(s) filed on An	nendment and R	CF of 27 October 2	006				
2a)[		his action is non-		<u> </u>				
3)								
٠,٠	closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.							
Disposit	ion of Claims		-,,					
·								
4)[	Claim(s) 1-18 is/are pending in the application.							
5\□	4a) Of the above claim(s) is/are withdrawn from consideration.							
	Claim(s) is/are allowed.							
	☑ Claim(s) <u>1-18</u> is/are rejected.							
	Claim(s) is/are objected to.	llor alastian rasu						
ا (٥	Claim(s) are subject to restriction and	nor election requ	irement.	•				
Applicat	ion Papers							
9) The specification is objected to by the Examiner.								
10) ☐ The drawing(s) filed on is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.								
	Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).							
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).								
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.								
Priority (	under 35 U.S.C. § 119							
	Acknowledgment is made of a claim for foreig ☐ All b)☐ Some * c)☐ None of:			-(d) or (f).				
	1. Certified copies of the priority documents have been received.							
	2. Certified copies of the priority documents have been received in Application No							
	3. Copies of the certified copies of the priority documents have been received in this National Stage							
	application from the International Bureau (PCT Rule 17.2(a)).							
* See the attached detailed Office action for a list of the certified copies not received.								
Attachmen	t(s)							
	e of References Cited (PTO-892)	4)	☐ Interview Summary	(PTO-413)				
2) 🔲 Notic	e of Draftsperson's Patent Drawing Review (PTO-948)		Paper No(s)/Mail Da	te				
3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date  5) Notice of Informal Patent Application  6) Other:								
ı-ape	. 140(5)/Wall Date	0)						

## **DETAILED ACTION**

1. Claims 1-18 are presented for consideration.

## Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1-3, 6, 7-8, 14-18 rejected under 35 U.S.C. 103(a) as being unpatentable over **Yoriki et al.** (US 6,640,431 B1) in view of **Trzecieski** (US 2003/0059194 A1).

Regarding claim 1, **Yoriki** discloses a multiple insertion head for mounting components onto substrates, comprising a carrier arranged such that it can rotate about a rotational axis (Fig. 2; Col. 1, lines 18-23), and a plurality of receiving tools arranged such that they can be moved in a mounting direction at an angle to the rotational axis (fig. 2, element 90); the receiving tools being arranged on the carrier and arranged so as to receive the components (Col. 1, line 59 to Col. 2, line 7), such that each receiving tool is provided with at least one of an active drive and sensors (Fig. 14, drives and sensors).

As for claims 2-3, 6, 7-8, 14-18, Yoriki further discloses,

- 2. Multiple insertion head according to claim 1, with each receiving tool having its own rotary drive by means of which received components can in each case be rotated about a tool axis arranged at an angle to the rotational axis (D) of the multiple insertion head (Fig. 14, nozzle rotating servo motor).
- 3. The multiple insertion head according to claim 1, wherein each receiving tool comprises a vacuum generator (Col. 1, lines 60-61, suction nozzle).
- 6. The multiple insertion head according to claim 1, further comprising a blast air vacuum device arranged in a receiving mounting position of one of the receiving tools, the vacuum device further arranged such that therein components can be received or mounted by means of the receiving tool located in the receiving mounting position, the receiving tool being connected such that an additional vacuum can be applied or generated to the receiving tools for receiving the components <u>or</u> in addition a blast air impulse while mounting the components in the receiving tool located in the receiving mounting position (Col. 1, lines 60-51, i.e. one suction nozzle holding, by suction, an EC; Col. 16, lines 5-9).
- 7. The multiple insertion head according to claim 1, wherein each receiving tool comprises a tool shaft embodied as a hollow shaft running coaxially to the tool axis and a rotary sensor arranged so as to detect an angle position of the tool shaft (Col. 16, lins 19-34 and lines 53-61).

- 8. The multiple insertion head according to claim 7, wherein each tool shaft comprises a vacuum pipettes at a distal end range (Col. 16, lines 6-15).
- 14. The multiple insertion head according to claim 1, wherein the carrier comprises at least one control device arranged so as to control and/or regulate the active drives and/or sensors (Fig. 14).
- 15. The multiple insertion head according to claim 14, wherein the control unit comprises at least one digital signal processor by means of which one or a plurality of the active drives or sensors can be controlled (Fig. 14).
- 16. The multiple insertion head according to claim 1, further comprising, a linear motor arranged such that a receiving tool found in the receiving mounting position can be moved in the mounting direction provided that the linear motor is engaged in the receiving tool (Fig. 14).
- 17. The multiple insertion head according to claim 16, further comprising an engaging element provided in each receiving tool so as to engage in an engaging piece of the runner of the linear motor (Col. 18, lines 42-46 and lines 64-66).
- 18. The multiple insertion head according to claim 16, further comprising an additional retracting means interacting with the linear motor by means of which a runner of the

linear motor is pretensioned by means of a spring tension against the force of gravity and in which the pretensioning is compensated for by compressed air when the insertion head is in operation (Col. 18, lines 42-62).

Yoriki discloses the limitations of claim 1 above but fails to disclose that each receiving tool is configured to be moved and controlled individually, and wherein components can be mounted independently of external actuators. However, Trzecieski discloses a multi axis component actuator wherein each receiving tool is configured to be moved and controlled individually, and wherein components can be mounted independently of external actuators (Fig. 6, i.e., components holders 31, linear actuators 22; [0038]-[0039]). Therefore, it would have been obvious to a person of the ordinary skill in the art at the time the invention was made to combine the component mounting apparatus of Yoriki with the component actuator of Trzecieski because it would provide active alignment of components due to its dynamic nature and compensation of variations in alignment due to temperature changes, epoxy hardening, solder expansion, fusing processes, and other effects resulting during a process of affixing aligned components one to another. Furthermore, such an alignment system provides for improved alignment speed as well significant cost reduction over conventional alignment systems (Trzecieski, [0042]).

## Claim Rejections - 35 USC § 103

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

Application/Control Number: 10/541,352

Art Unit: 2125

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 4-5 are rejected under 35 U.S.C. 103(a) as being unpatentable over

Yoriki et al. (US 6,640,431 B1) and Trzecieski, and further in view of Gieskes et al.

(US 2004/0074085 A1).

Yoriki discloses the limitations of claims 1 and 3 above but fails to disclose the limitations of claims 4-5. However, **Gieskes** discloses such limitations as follows:

- 4. The multiple insertion head according to claim 3, wherein the vacuum generators comprises a Venturi tubes and the carrier comprises a hollow shaft running coaxially to the rotational axis to which the receiving tools are fitted such that compressed air can be conveyed through the hollow shaft of the carrier to the Venturi tubes ([0026]).
- 5. The multiple insertion head according to claim 3, wherein the Venturi tubes is connected to a regulator to control pressure ([0028]-[0029]).

Therefore, it would have been obvious to a person of the ordinary skill in the art at the time the invention was made to combine the teachings of **Yoriki and Trzecieski** with the integrated air flow control for a pick and place spindle assembly as taught by **Gieskes** because it would provide an improved system by minimizing the time required for the vacuum for air pressure to be applied to the nozzle tip ([00.11]).

4. Claims 9-13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yoriki et al. (US 6,640,431 B1) and Trzecieski, and further in view of Asai et al. (US 5,588,195).

Yoriki discloses the limitations of claim 1 above but fails to disclose the limitations of claims 9-13. However, Asai discloses such limitations as follows:

- 9. The multiple insertion head according to claim 1, further comprising a rotationally symmetrical energy and data transmission device arranged between the carrier and a housing of the multiple insertion head, the transmission device arranged such that at least one of active drives and sensors can be supplied with energy and by which the data from the sensors and the data to the sensors can be transmitted with a first transmitter part being permanently fitted to the housing of the multiple insertion head and a second transmitter part being permanently fitted to the carrier in such a way that it can rotate (Abstract; Fig. 13; Col. 2, lines 55-67).
- 10. The multiple insertion head according to claim 9, wee wherein the transmission device hang-comprises at least one slip ring (Col. 2, lines 2-9).
- 11. The multiple insertion head according to claim 9, wherein the data transmission device comprises one pair of electromagnetic transmitters and one pair of capacitive transmitters arranged rotationally symmetrical around the rotational axis of the multiple insertion head and by means of which there is non-contact transmission of both the energy and the data (Col. 3, line 40 to Col. 4, lines 6).

Application/Control Number: 10/541,352

Art Unit: 2125

12. The multiple insertion head according to claim 11, wherein the capacitive

transmitter, comprises a plate-shaped antenna in the first transmitter part and in the

second transmitter part the first transmitter part the electromagnetic transmitter

comprises a circular magnetically conductive body with a u-shaped cross section open

in the direction of the carrier and a circular magnetically conductive body in the second

transmitter part comprising a rectangular cross section which is arranged in such a way

in the opening of the first transmitter part that the direction of the magnetic field used for

the transmission of energy is at right angles to the direction of the electrical field used

for the transmission of data (Fig. 8, element 316).

13. The multiple insertion head according to claim 9, comprising at least one polished

disk arranged on the housing and on the carrier such that the polished disks are

arranged immediately next to each other so that compressed air and a vacuum can be

applied from external vacuum generators to the active drives of the carrier (Col. 9, lins

30-44).

Therefore, it would have been obvious to a person of the ordinary skill in the art

at the time the invention was made to combine the teachings of Yoriki and Trzecieski

with the electronic component mounting apparatus of Asai because it would provide an

improved mounting apparatus with a high durability (Col. 1, lines 6-10; Col. 2, lines 25-

31).

Page 8

Application/Control Number: 10/541,352

Art Unit: 2125

Response to Arguments

Page 9

5. Applicant's arguments with respect to claim 1 have been considered but are moot

in view of the new ground(s) of rejection.

Conclusion

6. The prior art made of record and not relied upon is considered pertinent to

applicant's disclosure.

Any inquiry concerning communication or earlier communication from the

examiner should be directed to Zoila Cabrera, whose telephone number is (571) 272-

3738. The examiner can normally be reached on M-F from 8:00 a.m. to 5:30 p.m. EST

(every other Friday).

If attempts to reach the examiner by phone fail, the examiner's supervisor, Leo

Picard, can be reached on (571) 272-3749. Additionally, the fax phones for Art Unit

2125 are (571) 273-8300. Any inquiry of a general nature or relating to the status of this

application should be directed to the group receptionist at (703) 305-9600.

Zoila Cabrera Primary Examiner 1/22/07

ZOILA CABRERA PRIMARY EXAMINER TECHNOLOGY CENTER 2100

01/22/07